

4 Burner gas boiling top constructed from 304 stainless steel. 2mm pressed top, designed for flush alignment and to accommodate the water column accessory.

Top comprises 4 sealed burners with maximum output of 36mj each complete with flame failure and pilot light for continuous output control from 9mj to 36mj. Pilot burner and flame failure thermocouple are located underneath the main burner body, protected from accidental impact and any spills. Hob features rounded corners for ease of cleaning and trivets in enameled cast-iron (acid, alkali and flame resistant). IPX5 protection rating.

STANDARD FEATURES

- Heavy Duty 2mm thick pressed tops
- Modular design
- High efficiency burners
- IPX5 water rating
- Easy to clean
- Flame failure and pilot lights standard
- Hygiene valve collar on all front controls

OPTIONAL FEATURES

- Cabinet base
- Hygenic cabinet base
- Stand base
- Castors
- Flexible gas hose with quick disconnect and restraining kit



DIMENSIONS

External: 930D x 800W x 230H mm

TECHNICAL DATA

Gas Type: Natural or LP

Total Output: 144MJ

Burners: 4 x 36MJ

Gas Connection: 1/2"

AGA approval number: 7410

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

